# DART SERVICE INSTRUCTION

TO AMEND INSTRUCTIONS FOR CONTINUED AIRWORTHYINESS ICA-D350-794 REV. 6 OR EARLIER

REF. TCCA STC: SH05-4 REF. FAA STC: SR02794NY REF. EASA STC: 10031514 REF. BRAZIL STC: 2002S09-07/-08 REF. AUSTRALIAN STC: ASR063SY


#### **PURPOSE:**

The purpose of this Dart Service Instruction is to amend hardware changes to tank assembly D350-794-141 at change 002 and subsequent.


The NAS1149D0363J washers under the AN3H5A bolts have been replaced by NAS1149D0332J washers to allow greater thread grip. The MS35207-266 screws have been replaced by AN3-6A bolts to prevent the screw heads from becoming stripped during installation.

#### **FIGURE CORRECTIONS:**


Revise ICA-D350-794 Figure 28-2 and Figure 28-3 as follows:



### **ICA FIGURE 28-3 IS**



## **ICA FIGURE 28-3 WAS**



CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

BY: D. SHEPHER® (DE # 02)

DATE: 14,05,21
CERT. NO.: SH05-4
ISSUE NO.: 3

DESIGN	mage	DART AEROSPACE	LTD
DRAWN	Mer	HAWKESBURY, ONTARIO, CANADA	
CHECKED	AS	DRAWING NO.	REV. A
MFG. APPR.	10/A	DSI 9663	SHEET 2 OF 2
APPROVED	Tuff	TITLE	SCALE
DE APPR.		HARDWARE UPGRADE	NTS
DATE 13.09.16		COPYRIGHT © 2013 BY DART AEROSPACE LTD  THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS  NOT TO BE USED FOR ANY PURPOSE OR COPYED OR COMMINATE TO ANY OTHER PERSON WITHOUT  WITTEN PETRISSION FROM DART AEROSPACE LTD.	